

**REMARKS**


Applicant encloses an English translation of the application as originally filed with the International Bureau. In order to conform the specification to US practice, the Applicant has inserted description headings into the specification. In addition, the claims have been amended to remove multiple dependencies and conform them to US practice. So as to clarify the changes which have been made, Applicant respectfully requests that the enclosed substitute specification be accepted in lieu of the English translation of the application originally filed with the International Bureau. Applicant encloses both a copy with the changes marked with underlines (for additions) and cross-outs (for deletions) as well as a clean copy which incorporates the changes.

Applicant also respectfully requests that the substitute specification be further amended to include the requisite reference to the priority application.

The Commissioner is authorized to charge any additional fees that may be required to Deposit Account No. 50-0320.

Respectfully submitted,  
FROMMER LAWRENCE & HAUG LLP

By:

  
Ronald R. Santucci  
Reg. No. 28,988  
(212) 588-0800-

Method for communicating between a command transmitter  
and a command transmitter-receiver

Background of the invention

5 The invention relates to a method of communication  
between a command transmitter and a bi-directional  
command transmitter-receiver that are intended for the  
control of elements ensuring the security and/or  
10 comfort of a building, the communication of control  
commands from the command transmitter to the command  
transmitter-receiver or from the transmitter-receiver  
to other elements, being done by way of frequency-  
modulated RF signals. It relates moreover to a command  
15 transmitter-receiver for the implementation of this  
method and to an installation comprising such a command  
transmitter-receiver and transmitter.

An installation comprising command transmitters and  
command receivers is used for example to control  
20 motorized devices such as shutters, roller blinds or  
else to control lights or alarm systems.

These installations typically comprise one or more  
command transmitters. Each controlled device is  
25 associated with a command receiver. Provision may  
however be made for a command receiver to drive several  
devices.

When the command transmitters and the command receivers  
30 communicate remotely, in particular by using an  
electromagnetic signal and especially an RF signal, it  
is necessary, in one and the same installation, for the  
command transmitters to be paired with the command  
receivers.

35 This pairing procedure may take several forms.

Description of the prior art

Patent US 4,750,118 discloses a pairing procedure making it possible to record the respective identifiers of a plurality of command transmitters in a memory situated in a command receiver. During functional  
5 operation, the command receiver validates the commands received only after having ascertained that the latter originate from a command transmitter whose identifier has previously been recorded. This solution involves allocating an identifier to each command transmitter  
10 during its manufacture.

Another known solution consists in assigning a unique identifier to the command receiver. This identifier is communicated, during a programming operation, to each  
15 of the control command transmitters.

For example, patent US 5,148,159 describes a system in which the identifier of a command receiver is communicated to command transmitters through an  
20 asynchronous type serial transmission.

Other systems also propose, on the same principle, the random generation of the codes constituting the identifiers of the command receivers. These identifiers  
25 are sent from the command receivers to each command transmitter in such a way as to make the transmissions secure.

These procedures make it possible to avoid the need to  
30 allocate an identifier to each command transmitter at the time of its manufacture. However, they require, at the level of the command transmitters, means for the reception of the information, that is to say means of bi-directional communication.

35 These solutions increase the manufacturing costs and, especially, those of the command transmitters. They significantly increase the cost of a control system

insofar as several command transmitters are often used to communicate with a single command receiver. Such is the case for example for the control of the opening and closing of garage doors, wherein each user has a  
5 command transmitter.

Systems for simplified communication to a command transmitter are known from patent applications DE 196 24 410, EP 0 440 974 and DE 196 25 588.

10

Application DE 196 24 410 discloses a method of communicating a code from a command receiver to a command transmitter. This communication is carried out by virtue of a low-frequency inductive link. Systems of  
15 coils and capacitors are provided at the level of the command receiver or of a programming system and of each command transmitter so as to ensure the sending of the code. This low frequency link involves a shorter range than a high frequency link, but it makes it possible to  
20 reduce the costs as compared with a conventional high frequency communication.

Likewise, application EP 0 440 974 discloses an installation for communicating between command  
25 transmitters and bi-directional command receivers through different frequencies, so as to differentiate the range and the signals transmitted.

Application DE 196 25 588 discloses a method of  
30 communication allowing the sending of an identification code, firstly, from a command receiver to a command transmitter having a simplified receiving part, then from this command transmitter to another command transmitter identical to the previous one. This method  
35 makes it possible to simplify the means of reception of the command transmitters as regards the antenna and the multiplexer. The costs are therefore slightly reduced. The range of the communication is also lower.

Patent US 4,988,992 discloses a motorized garage door comprising a command transmitter and a command receiver. The transmitter comprises means of activation  
5 of a modulator making it possible to pass to a state in which the sending of signals is possible.

Likewise, application EP 1 267 021 discloses a transmitter comprising means of waking up a  
10 microprocessor ensuring the generation of signals to be sent.

#### Summary of the invention

The aim of the present invention is to propose a method  
15 of communication and a command transmitter-receiver affording a solution to the problem cited and improving the methods of communication and the command transmitters-receivers known from the prior art. In particular, the invention proposes a method of bi-  
20 directional communication between at least one command transmitter-receiver and a command transmitter whose manufacturing costs are low.

The method according to the invention is characterized  
25 in that, in a programming mode, the command transmitter-receiver activates and interrupts successively the transmission of electric signals normally used for communication by frequency modulation, so as to send information to the command  
30 transmitter by way of amplitude-modulated RF signals.

Insofar as the means of transmission of amplitude-modulated signals use the means of transmission of frequency-modulated signals that already exist, the  
35 costs of adaptation of the receiver allowing it to ensure the function of transmission of amplitude-modulated signals are low.

The amplitude modulation communication being implemented especially during pairing procedures, the limited range of this mode of communication does not constitute an inconvenience to the user and makes it possible to circumvent interference with other systems or manipulation errors.

The dependent claims 2 and 3 define variants of this method of communication.

10

The command transmitter-receiver consisting of frequency-modulated RF signals, comprises, according to the invention, an antenna linked to:

- means of reception of frequency-modulated RF signals, and to
- means of transmission of frequency-modulated RF signals.

It comprises means of activation and of disabling of the means of transmission for the implementation of the communication method previously defined.

Variant embodiments of the transmitter-receiver are defined by the dependent claims 5 to 7.

The invention further relates to an installation comprising at least one command transmitter-receiver as previously defined and at least one command transmitter furnished with means for transmitting frequency-modulated RF signals and with means for receiving amplitude-modulated RF signals.

The communications from the command transmitters to the command transmitters-receivers are carried out by frequency-modulated signals and the communications from the command transmitters-receivers to the command transmitters are carried out by amplitude-modulated signals.

Description of the drawings

The appended drawing represents, by way of examples, a command transmitter, and a command transmitter-receiver according to the invention.

5

Figures 1a to 1c are diagrams representing a command transmitter and two command transmitters-receivers as well as the various modes of communication occurring between them.

10

Figure 2 is a diagram of a command transmitter-receiver according to the invention.

15

Figure 3 is a diagram of a command transmitter according to the invention.

Description of the preferred embodiments

20

The control installation represented in Figures 1a to 1c comprises two command receivers 10, 30 and a command transmitter 20. The command receiver 10 exhibits a function of command transmission (symmetric bi-directional communication), so as to be able to communicate with other elements of the installation. However, for the purposes of clarity, although the command receiver 10 is a transmitter-receiver, in the description it is dubbed a "command receiver".

25

The command receiver 10 is able to receive control commands from the command transmitter 20 with which it is associated, in such a way as to drive a piece of comfort and/or security equipment of a building such as a door, a roller blind or an alarm installation. The command receiver 10 can also transmit commands to the other receiver 30 of the installation so as to drive, for example, another piece of equipment of the building. It can operate in ultra high frequency and bi-directionally.

30

35

The command transmitter 20 transmits commands by way of electromagnetic waves of radio type at ultra high frequency. The command transmitter 20 communicates with the command receiver 10 in an asymmetric bi-directional manner, that is to say the signals transmitted and received are not modulated in the same way.

The command transmitter 20 transmits frequency-modulated signals to the command receiver 10 as represented by the arrow 40, however, the command transmitter can receive only amplitude-modulated signals.

The command receiver 10 also communicates in an asymmetric bi-directional manner with the command transmitter 20. However, it communicates in a symmetric bi-directional manner with the command transmitter 30 able to receive frequency-modulated signals.

The command receiver 10 is able to transmit, and the command transmitter to receive, amplitude-modulated signals. This communication is based on a low bit rate amplitude modulation of the carrier of the frequency-modulated signal transmitted by the receiver 10. It has a range of the order of 50 cm to 1 m, lower than the range of the frequency-modulated signals.

The receiver 10, represented in figure 2, comprises a module 12 for transmitting and receiving frequency-modulated signals. This module is connected, on the one hand, to an antenna 11, and, on the other hand, to a logic processing unit 13. It comprises a circuit 121R for amplifying and filtering the signals received by the antenna 11 then a circuit 122R for demodulating the amplified signals. The output of the demodulation circuit is connected to the logic processing unit. Thus, the signals picked up by the antenna are converted through this transmission and reception



module 12 into a command that can be interpreted by the logic processing unit which controls a piece of equipment 14.

5 The module 12 for transmitting and receiving frequency-modulated signals further comprises a circuit 122E for modulating commands from the logic processing unit and a circuit 121E for amplifying these modulated signals, linked to the antenna. Thus, control commands can be  
10 sent from the command receiver 10 to the command receiver 30. The elements just previously described are present in the transmitters-receivers known from the prior art.

15 The circuit 122E for modulation is for example a VCO (Voltage Controlled Oscillator), therefore having an oscillation function. The circuit 121E may then be a simple interrupter for linking to the antenna or for short-circuiting the antenna.

20

However, the part of the receiver ensuring the signals transmission function exhibits additional elements. It exhibits in particular a module for control of the means of transmission (121E, 122E) of the transmission  
25 and reception module 12. This module makes it possible to control the transmission of an amplitude-modulated signal which corresponds to an identifier that the receiver 10 assigns for example in a random manner to the transmitter 20. The sending of such a signal is for  
30 example controlled by a means 140 controlling a placing of the command receiver into programming mode. The programming mode corresponds to a mode in which the receiver sends an item of information, of identification code type, to one or more command  
35 transmitters. The means 140 for placing in programming mode may for example consist of a push button equipping the command receiver 10 and being linked to its logic processing unit.

The sending of the amplitude-modulated signal is done over a short distance. When the receiver 10 is placed in programming mode, the logic processing unit  
5 generates on one of its outputs a signal composed for example of a series of low states and of high states corresponding to an identifier to be assigned to the command transmitter 20. This series of high states and of low states causes via the control module 130 a  
10 series of activation and disabling operations of the circuit 121E for amplifying the signals from the modulation circuit 122E. This consequently causes a series of transmissions and interruptions of transmissions of the carrier wave used normally for the  
15 frequency-modulation communication. An amplitude-modulated signal is thus obtained. The series of transmissions and of interruptions of transmission of the carrier constitutes the RF signal comprising the message or, in the present case, the identifier to be  
20 sent. The carrier wave can be transmitted at a given frequency that is fixed or variable during the amplitude-modulation communications.

The module 130 can also consist of an interrupter  
25 controlled by the logic processing unit 13 and connected in series with the supply circuit of the amplification circuit 121E.

Thus, any item of information can be sent at low bit  
30 rate from the command receiver 10 to the command transmitter 20. In particular, this item of information may consist of an identification code or an address characterizing the command receiver. This identifier (or address) is subsequently used by the command  
35 transmitter to authenticate itself with the command receiver, this time within the framework of a conventional sending of commands carried out via frequency-modulated signals.

The signal, amplitude-modulated, may easily be detected by an elementary reception module 210 integrated with the command transmitter 20. This command transmitter  
5 represented diagrammatically in figure 3 comprises a logic processing unit 23 linked, on the one hand, to a user interface 24 of keypad type and, on the other hand, to a circuit 22 for modulation and transmission of frequency-modulated signals. This circuit 22 is  
10 itself linked to a coupling device 21. The transmitter furthermore comprises, linked to the logic processing unit 23, an elementary reception module 210. This module allows the reception of amplitude-modulated signals originating from the receiver 10.

15 This elementary reception module 210 comprises a receiver circuit 211. It may be a receiver circuit of super-regenerative type consisting mainly of a transistor used in oscillation mode. The transistor is  
20 blocked in oscillation except for the frequency of the carrier wave used for the communication via frequency-modulated signals. The oscillations are thereafter amplitude-demodulated and shaped by a demodulation circuit 212 translating the signal sent by the receiver  
25 10. Such a type of reception circuit, of low cost, makes it possible easily to detect at low bit rate, two amplitude levels of an amplitude-modulated RF signal.

The elementary reception module 210 therefore makes it  
30 possible to receive an "on or off" signal from the transmitter-receiver 10 within a range radius of 50 cm to 1 m and to interpret this signal in the form of a binary code. This code is thereafter stored in a memory of the logic processing unit so as to be sent in the  
35 information frames constituting the control commands transmitted by the command transmitter.

The installation described comprises one command transmitter only. However, a plurality of command transmitters such as described, like a plurality of command receivers such as described may constitute an  
5 installation according to the invention.

Claims:

1. A method of communication between a command transmitter (20) and a bi-directional command transmitter-receiver (10) that are intended for the control of elements (14) ensuring the security and/or comfort of a building, the communication of control commands from the command transmitter (20) to the command transmitter-receiver (10) or from the transmitter-receiver (10) to other elements, being done by way of frequency-modulated RF signals, ~~characterized in that~~wherein, in a programming mode, the command transmitter-receiver (10) activates and interrupts successively the transmission of electric signals normally used for communication by frequency modulation, so as to send information to the command transmitter (20) by way of amplitude-modulated RF signals.

2. The method of communication as claimed in claim 1, ~~characterized in that~~wherein the information sent to the command transmitter (20) is a series of transmissions and of interruptions of transmissions of a carrier that are carried out by means of transmissions (121E, 122E) of frequency-modulated RF signals of the command transmitter-receiver.

3. The method of communication as claimed in claim 1 ~~or 2~~, ~~characterized in that~~wherein the information comprises an identification code.

4. A transmitter-receiver (10) of commands consisting of frequency-modulated RF signals, comprising an antenna (11) linked to:

- means of reception (121R, 122R) of frequency-modulated RF signals, and to
- means of transmission (121E, 122E) of frequency-modulated RF signals,

~~characterized in that it~~which comprises means (13, 130) of activation and of disabling of the means of transmission (121E, 122E) for the implementation of the method as claimed in ~~one of claims 1 to 3~~.

5

5. The transmitter-receiver (10) of commands as claimed in ~~the preceding claim 4~~, ~~characterized in that~~wherein the means (13, 130) of activation and of disabling allow the activation and disabling of an  
10 amplifying circuit (121E) of the transmission means.

6. The transmitter-receiver (10) of commands as claimed in claim 5, ~~characterized in that~~wherein the means (13, 130) of activation and of disabling of the  
15 amplifying circuit (121E) comprise a logic processing unit (13) and a control circuit (130).

7. The transmitter-receiver (10) of commands as claimed in ~~one of claims 5 or 6~~, ~~characterized in that~~wherein the means (13, 130) of activation and of  
20 disabling comprise means (130) of control of the power supply of the amplifying circuit (121E).

8. An installation comprising at least one command  
25 transmitter-receiver (10) as claimed in ~~one of claims 4 to 7~~ and at least one command transmitter (20) furnished with means (22) for transmitting frequency-modulated RF signals and with means (210) for receiving amplitude-modulated RF signals.

Abstract

The inventive method makes it possible to communicate between an order transmitter and a bi-directional order transmitter-receiver for controlling elements which ensure the security or comfort of a building. The transmission of control orders from the order transmitter to the order transmitter-receiver or from said order transmitter-receiver to ~~others~~ other elements is carried out by means of frequency modulated radioelectric signals. Said method is characterised in that in a programming mode, the order transmitter-receiver successively activates and interrupts the emission of electric signals traditionally used for communicating in a frequency modulation mode in such a way that it is possible to transmit data to the order transmitter by means of said frequency modulated radioelectric signals.